

Modified: Programming Barcodes for DS2208

Configuration name in Utility : Modified
Last Modified : 08-nov-23
Windows Filename : DS2208 met fout piep.scncfg
Plug-in Name : DS2208-COMMON SR MODELS-002
ADF Version : v1.1
Report Type : Only parameters changed from defaults shown



Barcodes 1 of 2

Modified: Programming Barcodes for DS2208

Configuration name in Utility :	Modified
Last Modified :	08-nov-23
Windows Filename :	DS2208 met fout piep.scnfcg
Plug-in Name :	DS2208-COMMON SR MODELS-002
ADF Version :	v1.1
Report Type :	Only parameters changed from defaults shown



Barcodes 2 of 2

Modified: Programming Barcodes for DS2208

Configuration name in Utility : Modified
Last Modified : 08-nov-23
Windows Filename : DS2208 met fout piep.scnfcfg
Plug-in Name : DS2208-COMMON SR MODELS-002
ADF Version : v1.1
Report Type : Only parameters changed from defaults shown



Set Factory Defaults

Cable Connection Settings

USB

USB Device Type	SNAPI
HID Polling Interval	8 msec
Fast HID Keyboard	Disable

IBM-RS485

PortAddress	None
-------------	------

Keyboard Wedge

Terminal Type	IBM AT Notebook
---------------	-----------------

Single RS232C

RS232 Host Types	Standard Host
Serial Response Timeout	Minimum - 2 Sec
Beep on BEL	Enable

Symbology (bar code type) Settings

Codabar

Codabar Length 1	5
------------------	---

Code 128

Code 128 Length 1	0
-------------------	---

Modified: Programming Barcodes for DS2208

Configuration name in Utility : Modified
Last Modified : 08-nov-23
Windows Filename : DS2208 met fout piep.scncfg
Plug-in Name : DS2208-COMMON SR MODELS-002
ADF Version : v1.1
Report Type : Only parameters changed from defaults shown



Code 128 Length 2	0
-------------------	---

Code 39

Code 39 Length 1	2
------------------	---

GS1 Databar

GS1 Databar Limited	Disable
GS1 Databar Expanded	Disable

Interleaved 2 of 5

Interleaved 2 of 5 Length 1	0
Interleaved 2 of 5 Length 2	0

Matrix 2 of 5

Matrix 2 of 5 Length 1	14
Matrix 2 of 5 Length 2	0

Other 2D Symbolologies

Data Matrix Inverse	Regular
QR Code	Disable

Symbology Security Level

Security Level	Level 0
----------------	---------

Modify Data- Advanced Data Formatting

Erase All Rules
Begin New Rule

Modified: Programming Barcodes for DS2208

Configuration name in Utility : Modified
Last Modified : 08-nov-23
Windows Filename : DS2208 met fout piep.scncfg
Plug-in Name : DS2208-COMMON SR MODELS-002
ADF Version : v1.1
Report Type : Only parameters changed from defaults shown



-
1. Send ASCII Key <CTRL B/START OF TEXT>
 2. Send All that remains
 3. Send ASCII Key <CTRL C/END OF TEXT>
- Save Rule

General Parameter Settings

System

Timeout Between Different Symbols	2
Unique Bar Code Reporting	Disable
Configuration File	Modified

Firmware:

CAADES00-001-R01